

EZ Plate® Dual Boiler Water Semi-Instantaneous Water Heater

Tank Series 600 Gal • AquaPLEX® Duplex Stainless Steel

Model Number	Amps @120V ①	A	B	Shipping Weight lbs
600-2 L 600A-TRBPDW	5	77	42	1990
900-2 L 600A-TRBPDW	5	77	42	2050
1200-2 L 600A-TRBPDW	5	77	42	2080
1800-2 L 600A-TRBPDW	7	77	42	2195
2400-2 L 600A-TRBPDW	7	77	42	2285
3000-2 L 600A-TRBPDW	7	77	42	2270
3600-2 L 600A-TRBPDW	11	74	42	2435
4500-2 L 600A-TRBPDW	11	74	42	2480
5400-2 L 600A-TRBPDW	13	78	51	2630



Refer to PV 8601, PV 8602 and PV 8603 for information on heat exchanger recoveries, pressure drop and boiler water flow requirements with various entering boiler water temperatures and domestic water temperatures.

Refer to PV 8600 for standard and optional equipment.

① Optional boiler water valve adds 2 amps total

Recommended service clearance is 18 inches on all sides.

Completed piping assembly is factory fit between the exchanger and tank and separated at unions (or flanges) for shipping. Tank and heat exchanger ship separately for field assembly to piping assembly. If using glycol, consult your representative.



PVI reserves the right to change the design and specification without notice.

Hot Water Solutions

PVI Industries • Fort Worth, TX

© 2023 PVI