

EZ Plate® Boiler Water Semi-Instantaneous Water Heater

Tank Series 400 Gal • AquaPLEX® Duplex Stainless Steel

Model Number	Amps @120V ①	A	B	C	Shipping Weight lbs
600 L 400A-TRBPDW	4	65	70	42	1310
900 L 400A-TRBPDW	4	65	70	42	1340
1200 L 400A-TRBPDW	4	65	70	42	1350
1800 L 400A-TRBPDW	5	65	70	42	1375
2400 L 400A-TRBPDW	5	65	70	42	1435
3000 L 400A-TRBPDW	5	65	70	42	1449
3600 L 400A-TRBPDW	8	72	70	42	1470
4500 L 400A-TRBPDW	8	72	70	51	1510
5400 L 400A-TRBPDW	9	72	70	51	1580
7200 L 400A-TRBPDW	14	77	81	51	1740


Refer to PV 8601, PV 8602 and PV 8603 for information on heat exchanger recoveries, pressure drop and boiler water flow requirements with various entering boiler water temperatures and domestic water temperatures.

Refer to PV 8600 for standard and optional equipment.

① Optional boiler water valve adds 2 amps total

Recommended service clearance is 18 inches on all sides.

Completed piping assembly is factory fit between the exchanger and tank and separated at unions (or flanges) for shipping. Tank and heat exchanger ship separately for field assembly to piping assembly. If using glycol, consult your representative.



PVI reserves the right to change the design and specification without notice.

Hot Water Solutions