

# TRICON GAS -CONDENSING WATER HEATER

AquaPLEX® STORAGE TANK (DUPLIX STAINLESS STEEL)

500 to 900 MBH • 300 Gallons Storage



## STANDARD FEATURES AND EQUIPMENT

### PERFORMANCE

- 90% thermal efficiency (per 10 CFR 431: ANSI Z21.10.3 @ 70°F to 140°F)
- 94% thermal efficiency at low fire from 40°F to 140°F
- < 20 ppm NOx

### PRESSURE VESSEL

- AquaPLEX® tank (duplex stainless steel)
- Storage tank ASME stamped and National Board Registered for 150 psi MAWP
- Nonferrous, removable fittings at all tank connections
- ASME-rated temperature and pressure relief valve
- Inspection opening /cleanout
- Fiberglass insulation
- Coated steel jacket panels
- Drain valve
- Tank pressure gauge

### HEAT EXCHANGER

- Three-pass, fire tube design
- AquaPLEX® fire tubes

### BURNER, OPERATING CONTROLS AND SAFETIES

- Pre-mix surface burner with proportionate gas/air
- Electronic flame safeguard with pre- and post-purge
- Combustion sequence panel lights including lockout
- Programmable electronic operating control with digital temperature readouts, adjustable from 75°F to 180°F
- Immersion temperature limiting device (high limit control)
- Terminals for remote on-off
- Flame failure audible alarm and indicating light with remote contacts
- Seamless VFD modulation

### WARRANTY AND SERVICE POLICY

- 15-year tank warranty (PV903A) ①
- 1-year burner and parts warranty (PV536) ①
- First-year cost-free service policy (PV551) ①

### CODES AND STANDARDS

- Intertek / ETL listed:
  - UL 795 / CSA CAN1-3.1
  - Stainless steel Category IV vent material single or double-wall
  - NSF 372 lead free
- ASHRAE 90.1 compliant

### MISCELLANEOUS

- Factory authorized startup
- Vent termination cap, 6-inch diameter
- Condensate "P" trap (provided for field installation)

① See complete warranties and service policies for full details.

PVI reserves the right to change the design and specification without notice.

## FACTORY OPTIONS PACKAGES

- 1** ACCESSORIES PACKAGE
  - Electronic low-water cutoff (auto reset)
  - High temperature limit (manual reset)
  - Relay and proving terminal for remote equipment
- 3** ALARM and COMMUNICATIONS PACKAGE
  - Alarm on any failure functionality with switched contacts for remote notification
  - 95dB local audible alarm with silencing switch
  - 485 serial cable to connect electronic operator to BAS (Modbus RTU)
- 4** CSD-1 COMPLIANT CONTROLS PACKAGE
  - Includes the "Accessories" Package
  - Test and manual-reset function for low-water cutoff
  - Non-recycle, single-try ignition
  - High and low gas pressure switches

## FACTORY INSTALLED INDIVIDUAL OPTIONS

- A** CSA-rated temperature and pressure relief valve(s)
- D** Direct combustion air filter
- N** Celsius functionality for operating control

## FIELD INSTALLED OPTIONS

Protocol gateways (consult factory)  
\_\_ Bacnet IP \_\_ Bacnet MSTP \_\_ Lonworks

Condensate neutralization kit (PN 140795)  
Vent termination caps (larger than standard)

## OPTIONAL SERVICE POLICY

Long-life service policy (PV559) ①

## CUSTOM CONFIGURATION

Consult representative for additional custom options

## PART NUMBER ORDERING SEQUENCE

BASE MODEL# + "PACKAGES" + "OPTIONS"

Example: 75 L 300APVIF-13A



PVI Industries, LLC  
Fort Worth, TX • (800) 784-8326 • www.pvi.com