



Cobrex® Instantaneous Steam Water Heater

Performance by Model Number

160°F Domestic Hot Water Delivered

5 PSI INLET STEAM PRESSURE							
Model No.	GPM Delivered (40°F to 160°F)	Inlet Steam	Product	Lbs/Hr	MBtuh	Steam Trap	Waterside
CCX 160-20-5	20	5	2	1250	1200	1-1/2	7 psi
CCX 160-30-5	30	5	2	1875	1800	2	
CCX 160-40-5	40	5	3	2500	2400	2	
CCX 160-50-5	50	5	4	3125	3000	1-1/2 (2 ea.)	
CCX 160-60-5	60	5	4	3750	3600	2 (2 ea.)	
CCX 160-75-5	75	5	6	4688	4500	2 (2 ea.)	10 psi

10 PSI INLET STEAM PRESSURE							
Model No.	GPM Delivered (40°F to 160°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 160-20-10	20	10	1	1259	1200	1-1/2	7 psi
CCX 160-30-10	30	10	2	1889	1800	1-1/2	
CCX 160-40-10	40	10	3	2518	2400	2	
CCX 160-50-10	50	10	4	3148	3000	1-1/2 (2 ea.)	
CCX 160-60-10	60	10	4	3778	3600	1-1/2 (2 ea.)	
CCX 160-75-10	75	10	6	4722	4500	2 (2 ea.)	10 psi
CCX 160-90-10	90	10	6	5666	5400	2 (2 ea.)	

15 PSI INLET STEAM PRESSURE							
Model No.	GPM Delivered (40°F to 160°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 160-20-15	20	15	1	1268	1200	1-1/2	7 psi
CCX 160-30-15	30	15	2	1903	1800	1-1/2	
CCX 160-40-15	40	15	3	2537	2400	1-1/2	
CCX 160-50-15	50	15	3	3171	3000	2	
CCX 160-60-15	60	15	4	3805	3600	1-1/2 (2 ea.)	
CCX 160-75-15	75	15	6	4757	4500	1-1/2 (2 ea.)	10 psi
CCX 160-90-15	90	15	6	5708	5400	2 (2 ea.)	