

**AquaPLEX® Storage Tank (unlined duplex alloy)
with EZ PLATE® Dual Boiler Water Heat Exchanger - Double-wall
150 Gallon Tank Series - Dimensions**



Model No.	Amps @120V ①	A	B	Shipping Weight Lbs.
600-2 L 150A-TRBPDW	5	57	65	1200
900-2 L 150A-TRBPDW	5	57	65	1260
1200-2 L 150A-TRBPDW	5	57	65	1290
1800-2 L 150A-TRBPDW	7	57	75	1400
2400-2 L 150A-TRBPDW	7	57	75	1495
3000-2 L 150A-TRBPDW	7	57	75	1480
3600-2 L 150A-TRBPDW	11	54	72	1645
4500-2 L 150A-TRBPDW	11	54	72	1690

Refer to PV 8601, PV 8602 and PV 8603 for information on heat exchanger recoveries, pressure drop and boiler water flow requirements with various entering boiler water temperatures and domestic water temperatures.

Refer to PV 8600 for standard and optional equipment.

① Optional boiler water valve adds 2 amps total


Recommended service clearance is 18 inches on all sides.



Completed piping assembly is factory fit between the exchanger and tank and separated at unions (or flanges) for shipping. Tank and heat exchanger ship separately for field assembly to piping assembly.



PVI INDUSTRIES, LLC
FORT WORTH, TX 76111
(800) 784-8326 • www.pvi.com



PVI RESERVES THE RIGHT TO CHANGE THE DESIGN
AND SPECIFICATION WITHOUT NOTICE.