


ISX Series Instantaneous Steam Water Heater



ORDERING INFORMATION

Select the system based on the delivered temperature, GPM and steam supply pressure



Model Prefix	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P
ISX-120 Series												
ISX	120	20	15	120	20	30	120	20	50	120	20	150
ISX	120	25	15	120	25	30	120	25	50	120	25	150
ISX	120	40	15	120	40	30	120	40	50	120	40	150
ISX	120	50	15	120	50	30	120	50	50	120	50	150
ISX	120	70	15	120	70	30	120	70	50	120	70	150
ISX	120	90	15	120	90	30	120	90	50	120	90	150

Model Prefix	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P
ISX-140 series												
ISX	140	20	15	140	20	30	140	20	50	140	20	150
ISX	140	25	15	140	25	30	140	25	50	140	25	150
ISX	140	40	15	140	40	30	140	40	50	140	40	150
ISX	140	50	15	140	50	30	140	50	50	140	50	150
ISX	140	70	15	140	70	30	140	70	50	140	70	150
ISX	140	90	15	140	90	30	140	90	50	140	90	150

Model Prefix	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P
ISX-160 series												
ISX	160	20	15	160	20	30	160	20	50	160	20	150
ISX	160	25	15	160	25	30	160	25	50	160	25	150
ISX	160	40	15	160	40	30	160	40	50	160	40	150
ISX	160	50	15	160	50	30	160	50	50	160	50	150
ISX	160	70	15	160	70	30	160	70	50	160	70	150

Model Prefix	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P	Temp out	GPM	Steam P
ISX-185 series												
ISX	185	20	15	185	20	30	185	20	50	185	20	150
ISX	185	25	15	185	25	30	185	25	50	185	25	150
ISX	185	40	15	185	40	30	185	40	50	185	40	150
ISX	185	50	15	185	50	30	185	50	50	185	50	150

Example: To order a system providing 140F water at a maximum flow rate of 45 gpm with a steam supply pressure of 50 psi, select model **ISX-140-45-50**

Contact your nearest PVI representative for assistance in sizing, other temperatures+A22, volume, pressure and pricing.