



Cobrex® Instantaneous Steam Water Heater

Performance by Model Number

140°F Domestic Hot Water Delivered

5 PSI INLET STEAM PRESSURE

Model No.	GPM Delivered (40°F to 140°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 140-20-5	20	5	1	1042	1000	1-1/2	7 psi
CCX 140-30-5	30	5	2	1563	1500	1-1/2	
CCX 140-40-5	40	5	3	2083	2000	2	
CCX 140-50-5	50	5	3	2604	2500	2	
CCX 140-60-5	60	5	4	3125	3000	1-1/2 (2 ea.)	
CCX 140-75-5	75	5	6	3906	3750	2 (2 ea.)	10 psi
CCX 140-90-5	90	5	6	4688	4500	2 (2 ea.)	
CCX 140-100-5	100	5	6	5208	5000	2 (2 ea.)	

10 PSI INLET STEAM PRESSURE

Model No.	GPM Delivered (40°F to 140°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 140-20-10	20	10	1	1049	1000	1-1/4	7 psi
CCX 140-30-10	30	10	2	1574	1500	1-1/2	
CCX 140-40-10	40	10	3	2099	2000	1-1/2	
CCX 140-50-10	50	10	3	2623	2500	2	
CCX 140-60-10	60	10	3	3148	3000	2	
CCX 140-75-10	75	10	6	3935	3750	1-1/2 (2 ea.)	10 psi
CCX 140-90-10	90	10	6	4722	4500	2 (2 ea.)	
CCX 140-120-10	120	10	6	6295	6000	2 (2 ea.)	15 psi

15 PSI INLET STEAM PRESSURE

Model No.	GPM Delivered (40°F to 140°F)	Inlet Steam Pressure (psi)	Product Configuration	Lbs/Hr Steam	MBtuh Output	Steam Trap Outlet Size NPT	Waterside ΔP
CCX 140-20-15	20	15	1	1057	1000	1-1/4	7 psi
CCX 140-30-15	30	15	1	1586	1500	1-1/2	
CCX 140-40-15	40	15	3	2114	2000	1-1/2	
CCX 140-50-15	50	15	3	2643	2500	2	
CCX 140-60-15	60	15	3	3171	3000	2	
CCX 140-75-15	75	15	6	3964	3750	1-1/2 (2 ea.)	10 psi
CCX 140-90-15	90	15	6	4757	4500	1-1/2 (2 ea.)	
CCX 140-120-15	120	15	6	6342	6000	2 (2 ea.)	15 psi