

Conquest® Semi-Instantaneous Gas Condensing Water Heater

900 to 1000 MBH • AquaPLEX® Duplex Stainless Steel

Standard Features and Equipment

Performance

- 95% thermal efficiency (per 10 CFR 431: ANSI Z21.10.3 @ 70°F to 140°F)
- Up to 99% thermal efficiency at low fire from 40°F to 140°F
- Low NOx emissions < 20 ppm NOx

Pressure Vessel

- AquaPLEX tank (duplex stainless steel)
- Storage tank ASME stamped and National Board Registered for 150 psi MAWP
- CSA and ASME rated T&P relief valve
- Fiberglass insulation
- Durable polyethylene jacket (100% recycled material)
- Bottom drain valve

Heat Exchanger

- AquaPLEX combustion chamber and fire tubes, helically-coiled, single pass, 100% submerged

Burner, Operating Controls and Safeties

- Pre-mix surface burner with proportional air/gas control
- Electronic operating system with integrated ignition and operating controls
 - Programmable electronic operator with digital temperature readouts, adjustable from 80°F to 180°F (consult factory for applications with ≥180°F delivered water)
 - Plain text heater status and fault indication with fault history
 - Alarm with remote contacts
 - Visual modulation rate
 - Manual-reset high temperature limit
 - Modbus RTU (RS-485)
 - BACnet MSTP (RS-485)²
- Electronic low-water cutoff with manual reset and test switch
- Remote on/off terminals
- Seamless modulation
- Louver or power venter relay and proving contacts

Warranty

- 15-year tank and heating surfaces warranty covering waterside and condensate corrosion, leakage, production of rusty water, material defects and workmanship (PV903A)¹
- First Year Limited Service Policy (PV551)¹

¹See complete warranty and service policy for full details
PVI reserves the right to change the design and specification without notice.

²Protocol conversion to BACnet IP or LonWorks requires field supplied and field installed router or gateway.

Codes and Standards

- DOE Compliance Certification Database
- Intertek / ETL listed
 - ANSI Z21.10.3 / CSA 4.3
 - PVC, CPVC or Centrotherm InnoFlue SW Polypropylene Category IV vent material
 - Zero-clearance and combustible floor installation
 - NSF-372 lead-free
- EPA/DOE Energy Star qualified
- ASHRAE 90.1 compliant

Miscellaneous

- Condensate "P" trap (provided for field installation)

Optional Equipment

- CSD-1 controls (adds high and low gas pressure switches)
- Propane operation (consult factory)
- Factory-authorized startup
- Condensate neutralization system (PN 140794)
- Air filtration box (PN 121850)
- Installation kit (PN 143404)
- DigiTemp® digital mixing valve (consult factory)
- AquaSolve scale control system (consult factory)



A WATTS Brand

Hot Water Solutions

PVI Industries • Fort Worth, TX
USA: T: (817) 335-9531 • Toll Free: (800) 784-8326 • PVI.com
Technical Support • (800) 433-5654 • Mon-Fri, 8 am - 5 pm CST/CDT

© 2020 PVI