



CSX Single Configuration when Producing 140°F Domestic Water from various supply steam pressures

	MODEL No.	Domestic Water Temperature °F	Domestic Water Delivered gpm	Steam Pressure Supplied psi	MBtu/h Input	Steam Flow in HX Lb /hr	Product Configuration	Steam Valve	Condensate Trap NPT
STEAM VALVE NOT REQUIRED	CSX-140-15-5	140	15	5	750	780	A	none	1-1/2
	CSX-140-30-5	140	30	5	1500	1561	B	none	2
	CSX-140-45-5	140	45	5	2250	2341	C	none	2
	CSX-140-60-5	140	60	5	3000	3122	D	none	2
	CSX-140-15-10	140	15	10	750	787	A	none	1-1/4
	CSX-140-30-10	140	30	10	1500	1574	A	none	1-1/2
	CSX-140-45-10	140	45	10	2250	2361	C	none	2
	CSX-140-60-10	140	60	10	3000	3148	C	none	2
	CSX-140-15-15	140	15	15	750	793	A	none	1-1/4
	CSX-140-30-15	140	30	15	1500	1586	A	none	1-1/2
	CSX-140-45-15	140	45	15	2250	2379	B	none	2
	CSX-140-60-15	140	60	15	3000	3172	C	none	2
CSX-140-75-15	140	75	15	3760	3962	D	none	2	
PRESSURE REDUCING VALVE REQUIRED	CSX-140-15-30	140	15	30	750	792	A	1-1/4	1-1/4
	CSX-140-30-30	140	30	30	1500	1586	A	1-1/2	1-1/2
	CSX-140-45-30	140	45	30	2250	2379	B	2	2
	CSX-140-60-30	140	60	30	3000	3172	C	3	2
	CSX-140-75-30	140	75	30	3760	3962	D	3	2
	CSX-140-15-50	140	15	50	750	792	A	3/4	1-1/4
	CSX-140-30-50	140	30	50	1500	1586	A	1-1/4	1-1/2
	CSX-140-45-50	140	45	50	2250	2379	B	2	2
	CSX-140-60-50	140	60	50	3000	3172	C	2-1/2	2
	CSX-140-75-50	140	75	50	3760	3962	D	2-1/2	2
	CSX-140-15-150	140	15	150	750	792	A	1/2	1-1/4
	CSX-140-30-150	140	30	150	1500	1586	A	3/4	1-1/2
	CSX-140-45-150	140	45	150	2250	2379	B	1	2
CSX-140-60-150	140	60	150	3000	3172	C	1-1/4	2	
CSX-140-75-150	140	75	150	3760	3962	D	1-1/4	2	