

MAXIM GAS/OIL - PACKAGED WATER HEATER with AquaPLEX® STORAGE TANK (DUPLEX STAINLESS STEEL)



STANDARD FEATURES and EQUIPMENT

PERFORMANCE

- 81% thermal efficiency

PRESSURE VESSEL

- AquaPLEX® tank (duplex stainless steel)
- ASME stamped and National Board Registered for 150 psi Maximum Allowable Working Pressure
- Temperature and pressure relief valve (ASME rated)
- Non-ferrous, removable tank fittings
- Inspection opening/cleanout
- Fiberglass insulation
- Coated steel jacket panels
- Drain valve
- Tie down anchor points on tank
- Water pressure gauge on drain piping

HEAT EXCHANGER

- AquaPLEX® fire tubes with baffles
- SCALEGUARD® tube sheet protection

BURNER, OPERATING CONTROLS AND SAFETIES

- Combination gas/oil burner
- Spark ignition
- Electronic flame safeguard with pre-purge
- Low-fire start on oil (1000 and 1200 MBH)
- Programmable electronic operating control with digital temperature readouts
- High-temperature limit
- Terminals for remote on-off

WARRANTY AND SERVICE POLICY

- 15-year tank warranty (PV902) ①
- 1-year burner and parts warranty (PV536) ①
- 1-year cost-free service policy (PV551) ①
Conditions exist outside of the continental United States

CODES AND STANDARDS

- Intertek/ETL listed
 - UL 732
 - UL 795
 - NSF 372 lead free
 - Not listed in Canada
- ASHRAE 90.1 compliant

MISCELLANEOUS

- Barometric damper
- Factory-authorized startup

① See complete warranties and service policies for full details.

PVI reserves the right to change the design and specification without notice.

FACTORY OPTIONS PACKAGES

- 1** ACCESSORIES PACKAGE
 - Electronic low-water cutoff (test and manual reset)
 - High temperature limit (manual reset)
 - Relay and proving terminal for remote equipment
- 3** ALARM and COMMUNICATIONS PACKAGE
 - Alarm on any failure functionality with switched contacts for remote notification
 - 95dB local audible alarm with silencing switch
 - 485 serial cable to connect electronic operator to BAS (Modbus RTU)

FACTORY INSTALLED INDIVIDUAL OPTIONS

- A** CSA-rated temperature and pressure relief valve(s)
- C** MASS code compliance
- N** Celsius functionality for operating control

FIELD INSTALLED OPTIONS

Protocol gateways (consult factory)
__ Bacnet IP __ Bacnet MSTP

OPTIONAL SERVICE POLICY

Long-life service policy (PV559) ①
Conditions exist outside of the continental United States

CUSTOM CONFIGURATION

Consult representative for all additional custom options

MODEL NUMBER SEQUENCE
BASE MODEL# + "PACKAGES" + "OPTIONS"
Example: 54-3.8 L 250APGO-13A