

Turbopower® 96 Condensing Gas Water Heater

AquaPLEX® Duplex Stainless Steel

Standard Features and Equipment

Performance

- 96% thermal efficiency (per 10 CFR 431: ANSI Z21.10.3 @ 70°F to 140°F)

Pressure Vessel

- AquaPLEX tank (duplex stainless steel)
- Storage tank ASME stamped and National Board Registered for 150 psi MAWP
- CSA-rated temperature and pressure relief valve(s) \leq 1300 MBH
- ASME-rated temperature and pressure relief valves @ 1600 MBH
- Fiberglass insulation
- Coated steel jacket panels
- Tie down anchor points on tank
- Bottom drain valve
- Tank pressure gauge
- Factory assembled pump and piping manifolds between tank and economizer includes press-form fittings (Viega and ProPress)

Heat Exchanger

- Primary: AquaPLEX combustion chamber and copper fire tubes
- Secondary: stainless steel economizer

Burner, Operating Controls and Safeties

- Pre-mix surface burner with zero-governor gas regulator and proportionate gas/air mixture
- Electronic operating system with integrated ignition and operating controls
 - Programmable electronic operator with digital temperature readouts, adjustable from 80°F to 180°F (consult factory for applications with \geq 180°F delivered water)
 - Plain text heater status and diagnostics with event history
 - Alarm with remote contacts
 - Manual-reset temperature limiting device
 - Modbus RTU, Bacnet MSTP connectable (RS-485)
- Electronic low-water cutoff with manual reset and test switch
- Remote on/off terminals
- Remote equipment relay and proving contacts (5 amp)
- Pressure relief valve for Economizer

Warranty

- 15-year full tank warranty covering corrosion, leakage, production of rusty water, material defects and workmanship (10 additional years prorated) (PV903A)¹
- 5-year full primary heat exchanger warranty (PV584)¹
- 1-year burner and parts warranty (PV536)¹
- First-year service policy (PV551)¹

¹See complete warranty and service policy for full details
PVI reserves the right to change the design and specification without notice.

²Protocol conversion to BACnet IP or LonWorks requires field supplied and field installed router or gateway.

Codes and Standards

- DOE Compliance Certification Database
- Intertek / ETL listed
 - ANSI Z21.10.3 / CSA 4.3
 - PVC, CPVC or Centrotherm InnoFlue SW Polypropylene Category IV vent material
 - NSF-372 lead-free
- ASHRAE 90.1 compliant

Miscellaneous

- Condensate "P" trap (provided for field installation)
- Factory authorized startup

Optional Equipment

- Condensate Neutralization system (up to 1000 MBH PN 140794)
- Condensate Neutralization system (up to 2000 MBH PN 140795)
- Consult representative for all additional custom options
- Long-life service policy (PV559)¹

Factory Options Packages

- CSD-1 compliant controls package: High and low gas pressure switches

Factory Installed Individual Options

- CSA-rated temperature and pressure relief valve(s) for model prefix 1600.
- Propane operation (consult factory)



A WATTS Brand

Hot Water Solutions

PVI Industries • Fort Worth, TX
USA: T: (817) 335-9531 • Toll Free: (800) 784-8326 • PVI.com
Technical Support • (800) 433-5654 • Mon-Fri, 8 am - 5 pm CST/CDT

© 2024 PVI