

DURAWATT® ELECTRIC • PACKAGED WATER HEATER

AquaPLEX® - STORAGE TANK (UNLINED DUPLEX ALLOY)

TANK SERIES 750 GALLONS - 208V, 3Ø

MODEL NUMBER	RECOVERY RATE GPH		INPUT kW	ELEMENT AMPS ** 208V, 3Ø	SHIPPING WEIGHT lbs
	40°-120°F	40°-140°F			
45 L 750A-VE	45	37	9	25	2010
90 L 750A-VE	90	70	18	50	2010
140 L 750A-VE	140	111	27	75	2010
180 L 750A-VE	180	150	36	100	2010
230 L 750A-VE	230	184	45	125	2020
270 L 750A-VE	270	220	54	150	2020
320 L 750A-VE	320	256	63	175	2020
370 L 750A-VE	370	300	72	200	2020
410 L 750A-VE	410	325	80	222	2030
460 L 750A-VE	460	368	90	251	2030
510 L 750A-VE	510	405	99	276	2030
540 L 750A-VE	540	430	105	292	2050
610 L 750A-VE	610	491	126	334	2060
690 L 750A-VE	690	552	135	376	2070
770 L 750A-VE	770	614	150	417	2080
840 L 750A-VE	840	675	165	459	2090
920 L 750A-VE	920	736	180	501	2100


ASHRAE 90.1 compliant.

For standard and optional equipment, see form #PV 8130.

Dimensions in inches, unless otherwise noted.

Contact PVI representative for higher inputs.

** For other voltages, see PV 8458.



STANDARD ELECTRICAL REQUIREMENTS:

CONTROL CIRCUIT TRANSFORMER SUPPLIED ON 480V ONLY. TAPPED CONTROL CIRCUIT INTERNALLY WIRED FOR 208V AND 240V.

208V AND 240V MODELS REQUIRE AC NEUTRAL CONDUCTOR FOR GROUNDING OF CONTROL CIRCUIT.

ALTERNATE VOLTAGES: FOR 230/460V, MULTIPLY kW AND RECOVERY BY .92. MULTIPLY AMPS BY .96.

FOR 220/440V, MULTIPLY kW AND RECOVERY BY .84. MULTIPLY AMPS BY .92.